



Type	max. Clock Rate (MHz)	ROM (Byte)	ROM Protection	RAM (Byte)	I/O Lines (Inputs only)	ADC-Inputs/Resolution	Timer/Counter (16-Bit)	Interrupt vectors/Levels	Serial I/O	FCAN 2.0B active	USB 1.0 Interface	PWM	Mul./Div. Unit	Data Pointers (16-Bit)	Hardware Power Down	Watch-dog Timer	Osc Watch-dog	Packaging	
C501G-L / -1R C501G-E	40	- / 8 k 8 k OTP	✓ ✓	256	32	-	3	6 / 2	USART	-	-	-	-	1	-	-	-	P-DIP-40 P-LCC-44 P-MQFP-44	Fully compatible with 80C52/ C32 standard
C504-L / -2R C504-2E	40	- / 16 16 k OTP	✓ ✓	512	32	8 / 10	4	12 / 2	USART	-	-	6-ch	-	1	-	✓	✓	P-MQFP-44	CCU for DC motor control, Interrupt wakeable Power down
C513-1R C513A-L/-R/-2R	12	8 k - 12 k / 16 k	-	256 512	32	-	3	7 / 2	USART + SSC	-	-	-	-	1	-	-	-	P-DIP-40/P-LCC-44 P-MQFP-44	Low Power Low EMI
C505L-4E	20 ²⁾	32 k OTP	-	512	46	8 / 10	3	12 / 4	USART	-	-	4-ch	-	8	-	✓	✓	P-MQFP-80	LCD Driver on-chip 128 segments; RTC with 32 kHz subclock
C505-L / -2R	20 ²⁾	- / 16 k	✓	512	34	8 / 8	3	12 / 4	USART	-	-	4-ch	-	8	-	✓	✓	P-MQFP-44	Enhanced power saving modes; Low EMI, Interrupt wakeable Power down
C505C-L / -2R	20 ²⁾	- / 16 k	✓	512	34	8 / 8	3	12 / 4	USART	✓	-	4-ch	-	8	-	✓	✓	P-MQFP-44	Enhanced power saving modes; Low EMI, Interrupt wakeable Power down
C505A-4E	20 ²⁾	32 k OTP	✓	1280	34	8 / 10	3	12 / 4	USART	-	-	4-ch	-	8	-	✓	✓	P-MQFP-44	Enhanced power saving modes; Low EMI, Interrupt wakeable Power down
C505CA-4E	20 ²⁾	32 k OTP	✓	1280	34	8 / 10	3	12 / 4	USART	✓	-	4-ch	-	8	-	✓	✓	P-MQFP-44	Enhanced power saving modes; Low EMI, Interrupt wakeable Power down
C515-L / -1R	24	- / 8 k	✓	256	56 (8)	Prog. REF 8 / 8	3	12 / 4	USART	-	-	4-ch	-	1	-	✓	✓	P-MQFP-80	Compatible with SAB 80C515
C515A-L / -4R	24	- / 32 k	✓	1280	56 (8)	8 / 10	3	12 / 4	USART	-	-	4-ch	-	1	✓	✓	✓	P-MQFP-80	Compatible with SAB 80C515A
C515C-L / -8R C515C-8E	10 ²⁾	- / 64 k 64 k OTP	✓	2304	57 (8)	8 / 10	3	15 / 4	USART + SSC	✓	-	4-ch	-	8	✓	✓	✓	P-MQFP-80	Low Power, Low EMI
C517A-L / 4R	24	- / 32 k	✓	2304	68 (12)	12 / 10	4	17 / 4	USART + UART	-	-	21-ch	✓	8	✓	✓	✓	P-MQFP-100	Compatible with SAB 80C517A
C509-L	16 ²⁾	-	-	3328	64 (15)	15 / 10	5	19 / 4	USART + UART	-	-	29-ch	✓	8	✓	✓	✓	P-MQFP-100	CMOS/TTL Ports Bootstrap
C540U-E ¹⁾	12 ²⁾	4 k OTP	✓	256	32 / 30	-	2	7 / 2	-	-	HUBless	-	-	1	-	-	-	P-SDIP-52 / P-LCC-44	USB-Transceiver-on-chip;
C541U-2E ¹⁾	12 ²⁾	8 k OTP	✓	256	32 / 30	-	2	7 / 2	SSC	-	HUBless	-	-	1	-	✓	✓	P-SDIP-52 / P-LCC-44	USB-Transceiver-on-chip;
SAB 80C515 SAB 80C535	20	8 k -	✓ -	256	56 (8)	Prog. REF 8 / 8	3	12 / 4	USART	-	-	4-ch	-	1	-	✓	-	P-LCC-68	
SAB 80C515A SAB 83C515A-5	18	- 32 k	- ✓	1280	56 (8)	8 / 10	3	12 / 4	USART	-	-	4-ch	-	1	✓	✓	✓	P-LCC-68	
SAB 80C517 SAB 80C537	16	8 k -	✓ -	256	68 (12)	Prog. REF 12 / 8	4	14 / 4	USART + UART	-	-	21-ch	✓	8	-	✓	✓	P-LCC-84	
SAB 80C517A SAB 83C517A-5	18	- 32 k	- ✓	2304	68 (12)	12 / 10	4	17 / 4	USART + UART	-	-	21-ch	✓	8	✓	✓	✓	P-LCC-84	

¹⁾ under development ²⁾ CPU-Clock